NSN 4720-00-715-2555

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-715-2555
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
Between 0.173 inches and 0.203 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
Between 0.304 inches and 0.344 inches
Minimum Inside Bending Radius:
2.000 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
12000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.438 inches 1st end

Seat Angle:

37.0 degrees 1st end **Hydrostatic Test Pressure:**

3000.0 pounds per square inch

Outer Covering Environmental Protection:

Corrosion resistant and fuel resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

11.875 inches working and 12.125 inches working

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unjf 1st end

NSN 4720-00-715-2555

Nonmetallic Hose Assembly - Page 2 of 2



Spec	ifica	ation	Data:
------	-------	-------	-------

88277-s2554441 manufacturers source control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0