## NSN 4720-00-715-5629

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-715-5629

Cross Sectional Shape:						
Round						
Thread Class:						
3b 1st end						
Thread Direction:						
Right-hand 1st end						
Inside Diameter:						
0.312 inches						
Tempurature Rating:						
-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response						
Outside Diameter:						
0.672 inches						
Minimum Inside Bending Radius:						
4.000 inches						
Connection Style:						
Swivel nut flare 2nd end						
End Connection Design:						
Straight 1st end						
Connection Type:						
Threaded internal tube 1st end						
Burst Test Pressure:						
9000.0 pounds per square inch						
Layer Composition And Location:						
1st layer braided fiber and 2nd layer braided steel wire and outer layer rubber impregnated woven fabric						
Maximum Operating Pressure:						
2000.0 pounds per square inch						
Thread Size:						
0.562 inches 2nd end						
Seat Angle:						
37.0 degrees 2nd end						
Hydrostatic Test Pressure:						
4500.0 pounds per square inch						
Flow Angle:						
90.0 degrees 2nd end						
Outer Covering Environmental Protection:						
Oil resistant						
Inside Surface Condition:						
Smooth						
Measuring Method And Length:						
33.750 inches working						

Media For Which Designed:
Fuel/oil, hydrocarbon single response

## NSN 4720-00-715-5629

Nonmetallic Hose Assembly - Page 2 of 2



	••		•	_		
ı	hre	ลด	Seri	26 I I	PSIU	nator:
•		uu	CCII		COIG	mator.

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0