NSN 4720-00-718-6024

81349-mil-h-370 government specification

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-718-6024

Cross Sectional Shape:
Round
Inside Diameter:
2.000 inches
Tempurature Rating:
-32.0 degrees celsius and 52.0 degrees celsius single response
Outside Diameter:
2.656 inches
Minimum Inside Bending Radius:
6.000 inches
Exterior Color:
Black
Quick Disconnect Size:
2.000 inches 2nd end
End Application:
Tank, pumping unit
Connection Style:
Cam or lever (external) 2nd end
End Connection Design:
Straight 2nd end
Connection Type:
Internal quick disconnect 1st end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
500.0 pounds per square inch
Layer Composition And Location:
1st layer rubber impregnated braided cotton cord and 2nd layer spirally wrapped steel fabric and outer layer molded rubber, synthetic
Hydrostatic Test Pressure:
150.0 pounds per square inch
Outer Covering Environmental Protection:
Abrasion resistant and fuel resistant and oil resistant and ozone resistant
Criticality Code Justification:
Feat
Inside Surface Condition:
Smooth
Measuring Method And Length:
3.7 feet
Special Features:
Weapon system essential
Specification Data:

NSN 4720-00-718-6024

Nonmetallic Hose Assembly - Page 2 of 2



Specification Or Standard:
2 type and 6 size
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A542a0

Mil-std (military Standard):

Mil-prf-370 spec.