Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-718-8873

Cross Sectional Shape: Round Thread Class: 2b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.375 inches Tempurature Rating: -65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.781 inches Minimum Inside Bending Radius: 5.000 inches Connection Style: Swivel nut, inverted flare 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Reusable end fittings Thready Qty Per Inch (tpi): 18 1st end Burst Test Pressure: 9000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber, chloroprene Maximum Operating Pressure: 250.0 pounds per square inch
Thread Class: 2b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.375 inches Tempurature Rating: -65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.781 inches Minimum Inside Bending Radius: 5.000 inches Connection Style: Sovivel nut, inverted flare 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Reusable end fittings Thready Qty Per Inch (tpi): 18 1st end Burst Test Pressure: 9000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber, chloroprene Maximum Operating Pressure:
2b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.375 inches Tempurature Rating: -65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.781 inches Minimun Inside Bending Radius: 5.000 inches Connection Style: Swivel nut, inverted flare 2nd end End Connection Design: Straight 1st end Connection Type: Thready Gty Per Inch (tpi): 18 1st end Burst Test Pressure: 9000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber, chloroprene
Thread Direction: Right-hand 1st end Inside Diameter: 0.375 inches Tempurature Rating: -65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.781 inches Minimum Inside Bending Radius: 5.000 inches Connection Style: Swivel nut, inverted flare 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Reusable end fittings Thready Qty Per Inch (tpi): 18 1st end Burst Test Pressure: 9000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber, chloroprene Maximum Operating Pressure:
Right-hand 1st end Inside Diameter: 0.375 inches Tempurature Rating: -65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.781 inches Minimun Inside Bending Radius: 5.000 inches Connection Style: Swivel nut, inverted flare 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Reusable end fittings Thready Qty Per Inch (tpi): 18 1st end Burst Test Pressure: 9000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber, chloroprene
Inside Diameter: 0.375 inches Tempurature Rating: -65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.781 inches Minimun Inside Bending Radius: 5.000 inches 5.000 inches Connection Style: Swivel nut, inverted flare 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Reusable end fittings Thready Qty Per Inch (tpi): 18 1st end Burst Test Pressure: 9000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber, chloroprene Maximum Operating Pressure:
0.375 inches Tempurature Rating: -65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.781 inches Minimum Inside Bending Radius: 5.000 inches 5.000 inches Connection Style: Swivel nut, inverted flare 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Reusable end fittings Thready Qty Per Inch (tpi): 18 1st end Burst Test Pressure: 9000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber, chloroprene Maximum Operating Pressure:
Tempurature Rating: -65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.781 inches Minimum Inside Bending Radius: 5.000 inches Connection Style: Swivel nut, inverted flare 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Reusable end fittings Thready Qty Per Inch (tpi): 18 1st end Burst Test Pressure: 9000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber, chloroprene Maximum Operating Pressure:
 -65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.781 inches Minimun Inside Bending Radius: 5.000 inches Connection Style: Swivel nut, inverted flare 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Reusable end fittings Thready Qty Per Inch (tpi): 18 1st end Burst Test Pressure: 9000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber, chloroprene Maximum Operating Pressure:
Outside Diameter:0.781 inchesMinimun Inside Bending Radius:5.000 inchesConnection Style:Swivel nut, inverted flare 2nd endEnd Connection Design:Straight 1st endConnection Type:Threaded internal tube 1st endFeatures Provided:Reusable end fittingsThready Qty Per Inch (tpi):18 1st endBurst Test Pressure:9000.0 pounds per square inchLayer Composition And Location:1st layer braided steel wire and outer layer molded rubber, chloropreneMaximum Operating Pressure:
0.781 inches Minimum Inside Bending Radius: 5.000 inches Connection Style: Swivel nut, inverted flare 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Reusable end fittings Thready Qty Per Inch (tpi): 18 1st end Burst Test Pressure: 9000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber, chloroprene Maximum Operating Pressure:
Minimum Inside Bending Radius: 5.000 inches Connection Style: Swivel nut, inverted flare 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Reusable end fittings Thready Qty Per Inch (tpi): 18 1st end Burst Test Pressure: 9000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber, chloroprene Maximum Operating Pressure:
5.000 inches Connection Style: Swivel nut, inverted flare 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Reusable end fittings Thready Qty Per Inch (tpi): 18 1st end Burst Test Pressure: 9000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber, chloroprene Maximum Operating Pressure:
Connection Style: Swivel nut, inverted flare 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Reusable end fittings Thready Qty Per Inch (tpi): 18 1st end Burst Test Pressure: 9000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber, chloroprene Maximum Operating Pressure:
Swivel nut, inverted flare 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Reusable end fittings Thready Qty Per Inch (tpi): 18 1st end Burst Test Pressure: 9000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber, chloroprene Maximum Operating Pressure:
End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Reusable end fittings Thready Qty Per Inch (tpi): 18 1st end Burst Test Pressure: 9000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber, chloroprene Maximum Operating Pressure:
Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Reusable end fittings Thready Qty Per Inch (tpi): 18 1st end Burst Test Pressure: 9000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber, chloroprene Maximum Operating Pressure:
Connection Type: Threaded internal tube 1st end Features Provided: Reusable end fittings Thready Qty Per Inch (tpi): 18 1st end Burst Test Pressure: 9000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber, chloroprene Maximum Operating Pressure:
Threaded internal tube 1st end Features Provided: Reusable end fittings Thready Qty Per Inch (tpi): 18 1st end Burst Test Pressure: 9000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber, chloroprene Maximum Operating Pressure:
Features Provided: Reusable end fittings Thready Qty Per Inch (tpi): 18 1st end Burst Test Pressure: 9000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber, chloroprene Maximum Operating Pressure:
Reusable end fittings Thready Qty Per Inch (tpi): 18 1st end Burst Test Pressure: 9000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber, chloroprene Maximum Operating Pressure:
Thready Qty Per Inch (tpi): 18 1st end Burst Test Pressure: 9000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber, chloroprene Maximum Operating Pressure:
 18 1st end Burst Test Pressure: 9000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber, chloroprene Maximum Operating Pressure:
Burst Test Pressure: 9000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber, chloroprene Maximum Operating Pressure:
9000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber, chloroprene Maximum Operating Pressure:
Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber, chloroprene Maximum Operating Pressure:
1st layer braided steel wire and outer layer molded rubber, chloroprene Maximum Operating Pressure:
Maximum Operating Pressure:
2250.0 pounds per square inch
Thread Size:
0.625 inches 2nd end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
4500.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Outer Covering Environmental Protection:
Outer Covering Environmental Protection: Oil resistant and ozone resistant and mildew resistant
-

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length: 73.375 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Unf 2nd end Shelf Life: N/a Unit Of Measure: --

No

Fiig:

A542a0