

NSN 4720-00-721-9561 Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-00-721-9561

0	ational Change
Round	ctional Shape:
Thread Cl	
3b 1st end	
Thread Di	
Right-hand	
Inside Dia	
0.313 inch	
	ture Rating:
	rees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside D	
0.446 inch	
	Inside Bending Radius:
4.000 inch	nes
Exterior C	Color:
Natural	
Connection	on Style:
Swivel nut	t flare 1st end
End Conr	nection Design:
Straight 1s	st end
Connection	on Type:
Threaded	internal tube 1st end
Features	Provided:
Electrosta	tic discharge capability
Burst Tes	et Pressure:
9000.0 po	unds per square inch
Layer Co	mposition And Location:
Outer laye	er braided corrosion resistant steel wire
Maximum	Operating Pressure:
1500.0 po	unds per square inch
Thread Si	ize:
0.562 inch	nes 1st end
Seat Angl	le:
27 0 do ar	age 1st and

37.0 degrees 1st end

Hydrostatic Test Pressure:

3000.0 pounds per square inch

Outer Covering Environmental Protection:

Corrosion resistant

Vacuum In Torr:

50.8

Inside Surface Condition:

Smooth

NSN 4720-00-721-9561

Fiig: A542a0

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length:
20.000 inches working
Special Features:
External support consists of butyl impregnated asbestos fire sleeve
Thread Series Designator:
Unjf 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No