NSN 4720-00-722-0172

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-722-0172

| Cross Sectional Shape: |
|---|
| Round |
| Thread Class: |
| 2b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.188 inches |
| Tempurature Rating: |
| -40.0 degrees fahrenheit and 275.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.516 inches |
| Minimum Inside Bending Radius: |
| 3.000 inches |
| Connection Style: |
| Swivel nut flare 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Thready Qty Per Inch (tpi): |
| 20 1st end |
| Burst Test Pressure: |
| 12000.0 pounds per square inch |
| Layer Composition And Location: |
| 1st layer braided cotton cord and 2nd layer braided steel wire and outer layer rubber impregnated braided cotton cord |
| Maximum Operating Pressure: |
| 3000.0 pounds per square inch |
| Thread Size: |
| 0.438 inches 1st end |
| Seat Angle: |
| 37.0 degrees 1st end |
| Vacuum In Torr: |
| 50.8 |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 142.500 inches working |
| Media For Which Designed: |
| Air and fuel/oil, hydrocarbon single response |
| Thread Series Designator: |

Unf 1st end

NSN 4720-00-722-0172

Nonmetallic Hose Assembly - Page 2 of 2



| _ | | | | | |
|---|----|------|---|--------|--|
| c | hο | JIF. | | .ife: | |
| J | | | _ | .II C. | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0