Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-723-2955

Cross Sectional Sh	ape:
Round	
Thread Class:	
2b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
1.812 inches	
Tempurature Rating	g:
-40.0 degrees fahrer	heit and 275.0 degrees fahrenheit single response
Outside Diameter:	
2.219 inches	
Minimum Inside Be	nding Radius:
13.250 inches	
Connection Style:	
Swivel nut flare 1st e	and
End Connection De	esign:
Straight 1st end	
Connection Type:	
Threaded internal tu	be 1st end
Thready Qty Per Inc	ch (tpi):
12 1st end	
Burst Test Pressur	e:
1400.0 pounds per s	quare inch
Layer Composition	And Location:
1st layer braided cot	ton cord and 2nd layer braided steel wire and outer layer rubber impregnated braided cotton cord
Maximum Operatin	g Pressure:
350.0 pounds per sq	uare inch
Thread Size:	
2.500 inches 1st end	I
Seat Angle:	
37.0 degrees 1st end	t
Vacuum In Torr:	
482.6	
Inside Surface Con	dition:
Smooth	
Measuring Method	And Length:
106.688 inches wor	king
Media For Which D	esigned:
Air and fuel/oil, hyd	rocarbon single response
Thread Series Desi	gnator:
Un 1st end	

NSN 4720-00-723-2955

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0

