## NSN 4720-00-724-0017

**Cross Sectional Shape:** 

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-724-0017

Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
Between 0.173 inches and 0.203 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
Between 0.304 inches and 0.343 inches
Minimum Inside Bending Radius:
2.000 inches
Angle Between Rigid Elbow Fittings In Deg:
15.0
Connection Style:
Swivel nut, flareless 1st end
End Connection Design:
Elbow 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability and reusable end fittings
Burst Test Pressure:
12000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
12.0 degrees 1st end
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Flow Angle:

50.8

90.0 degrees 1st end

Corrosion resistant

Vacuum In Torr:

**Outer Covering Environmental Protection:** 

## NSN 4720-00-724-0017

Nonmetallic Hose Assembly - Page 2 of 2



Inside Surface Condition:
Smooth
Measuring Method And Length:
7.875 inches working
Thread Series Designator:
Unjf 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A542a0