## NSN 4720-00-724-4458

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-724-4458

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.281 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response
Outside Diameter:
0.484 inches
Minimum Inside Bending Radius:
2.250 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Thready Qty Per Inch (tpi):
20 1st end
Burst Test Pressure:
6000.0 pounds per square inch
Layer Composition And Location:
1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1000.0 pounds per square inch
Thread Size:
0.500 inches 1st end
Seat Angle:
37.0 degrees 1st end
37.0 degrees 1st end  Hydrostatic Test Pressure:
Hydrostatic Test Pressure:
Hydrostatic Test Pressure: 3000.0 pounds per square inch
Hydrostatic Test Pressure: 3000.0 pounds per square inch Outer Covering Environmental Protection:

22.000 inches

**Measuring Method And Length:** 

## NSN 4720-00-724-4458

Nonmetallic Hose Assembly - Page 2 of 2



Media	For	Which	Design	ed

Fuel/oil, hydrocarbon single response

**Thread Series Designator:** 

Unf 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A542a0