Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-725-9207

C	ross Sectional Shape:
R	ound
Tł	nread Class:
3Ł	o 1st end
Tł	nread Direction:
Ri	ight-hand 1st end
In	side Diameter:
0.	188 inches
Te	empurature Rating:
-6	5.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
0	utside Diameter:
0.	312 inches
C	onnection Style:
S١	wivel nut flare 2nd end
Eı	nd Connection Design:
St	traight 1st end
C	onnection Type:
Tł	nreaded internal tube 1st end
Fe	eatures Provided:
EI	ectrostatic discharge capability and nuts drilled for lockwire
В	urst Test Pressure:
12	2000.0 pounds per square inch
La	ayer Composition And Location:
0	uter layer braided corrosion resistant steel wire
Μ	aximum Operating Pressure:
15	500.0 pounds per square inch
Tł	nread Size:
0.	438 inches 1st end
Se	eat Angle:
37	7.0 degrees 2nd end
H	ydrostatic Test Pressure:
30	000.0 pounds per square inch
FI	ow Angle:
90	0.0 degrees 2nd end
Va	acuum In Torr:
50).8
In	side Surface Condition:
Sr	mooth
Μ	easuring Method And Length:
6.	250 inches working
S	pecial Features:
N	uts drilled for safety wire

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:

Unf 2nd end

Specification Data:

07482-j264b0062db manufacturers source control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0