Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-726-5974

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.688 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response
Outside Diameter:
0.938 inches
Minimum Inside Bending Radius:
4.500 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
3750.0 pounds per square inch
Layer Composition And Location:
1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1000.0 pounds per square inch
Thread Size:
1.062 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
2000.0 pounds per square inch
Outer Covering Environmental Protection:
Abrasion resistant and corrosion resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
8.000 inches working

NSN 4720-00-726-5974 Nonmetallic Hose Assembly - Page 2 of 2 AeroBase Group

Media For Which Designed:

Air and fuel/oil, hydrocarbon single response

Thread Series Designator:

Unj 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0