NSN 4720-00-727-1339

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-727-1339

View Online at https://aerobasegroup.com/nsn/4720-00-727-1339					
Cross Sectional Shape:					
Round					
Inside Diameter:					
4.000 inches					
Tempurature Rating:					
-32.0 degrees fahrenheit single response					
Outside Diameter:					
4.750 inches					
Minimum Inside Bending Radius:					
16.000 inches					
Quick Disconnect Size:					
4.000 inches 2nd end					
Connection Style:					
Cam or lever (external) 2nd end					
End Connection Design:					
Straight 2nd end					
Connection Type:					
Internal quick disconnect 1st end					
Features Provided:					
Electrostatic discharge capability					
Burst Test Pressure:					
300.0 pounds per square inch					
Layer Composition And Location:					
2nd layer helix steel coil and outer layer molded rubber, chloroprene					
Maximum Operating Pressure:					
75.0 pounds per square inch					
Hydrostatic Test Pressure:					
100.0 pounds per square inch					
Outer Covering Environmental Protection:					
Fuel resistant and oil resistant and mildew resistant and ozone resistant					
Inside Surface Condition:					
Smooth					
Measuring Method And Length:					
141.000 inches working and 147.000 inches working					
Special Markings:					
Liquid fuel					
Specification Data:					
81349-mil-h-370 government specification					
Specification Or Standard:					
2 type and 9 size					
Shelf Life:					

N/a

NSN 4720-00-727-1339

Nonmetallic Hose Assembly - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-h-370 spec.