NSN 4720-00-727-1339

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-727-1339

View Online at https://aerobasegroup.com/nsn/4720-00-727-1339
Cross Sectional Shape:
Round
Inside Diameter:
4.000 inches
Tempurature Rating:
-32.0 degrees fahrenheit single response
Outside Diameter:
4.750 inches
Minimum Inside Bending Radius:
16.000 inches
Quick Disconnect Size:
4.000 inches 2nd end
Connection Style:
Cam or lever (external) 2nd end
End Connection Design:
Straight 2nd end
Connection Type:
Internal quick disconnect 1st end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
300.0 pounds per square inch
Layer Composition And Location:
2nd layer helix steel coil and outer layer molded rubber, chloroprene
Maximum Operating Pressure:
75.0 pounds per square inch
Hydrostatic Test Pressure:
100.0 pounds per square inch
Outer Covering Environmental Protection:
Fuel resistant and oil resistant and mildew resistant and ozone resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
141.000 inches working and 147.000 inches working
Special Markings:
Liquid fuel
Specification Data:
81349-mil-h-370 government specification
Specification Or Standard:
2 type and 9 size
Shelf Life:

N/a

NSN 4720-00-727-1339

Nonmetallic Hose Assembly - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-h-370 spec.