Nonmetallic Hose Assembly - Page 1 of 2



View Online a	at https://aerobasegroup.com/nsn/4720-00-727-1627
Cross Sectio	nal Shape:
Round	
Thread Direc	tion:
Right-hand 1s	st end
Inside Diame	eter:
0.250 inches	
Tempurature	Rating:
-60.0 degrees	s fahrenheit and 200.0 degrees fahrenheit single response
Outside Dian	neter:
0.625 inches	
Connection \$	Style:
Plain optional	end 1st end
End Connect	tion Design:
Straight 2nd e	and
Connection ⁻	Гуре:
Threaded inte	ernal pipe 1st end
Thready Qty	Per Inch (tpi):
18 2nd end	
Burst Test P	ressure:
900.0 pounds	per square inch
Layer Compo	osition And Location:
1st layer braid	ded cotton cord and outer layer rubber impregnated braided rayon cord
Thread Size:	
0.250 inches	2nd end
Outer Coveri	ng Environmental Protection:
Abrasion resis	stant and fuel resistant and oil resistant and ozone resistant and cold resistant
Inside Surfac	ce Condition:
Smooth	
Measuring M	ethod And Length:
16.000 inches	5
Special Mark	ings:
Oz	
Media For W	hich Designed:
Air single resp	Donse
Thread Serie	s Designator:
Nptf 2nd end	
Specification	n Data:
81349-mil-h-3	3992 government specification
Specification	o Or Standard:
1 type and 1 o	class
Shelf Life:	
N/a	

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-h-3992 spec.