

View Online at <https://aerobasegroup.com/nsn/4720-00-728-3220>

Cross Sectional Shape:

Round

Thread Class:

2a 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.313 inches

Temperature Rating:

-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response

Outside Diameter:

0.592 inches

Connection Style:

Swivel nut, inverted flare 1st end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded external tube 1st end

Thready Qty Per Inch (tpi):

18 1st end

Burst Test Pressure:

4000.0 pounds per square inch

Layer Composition And Location:

1st layer braided steel wire and outer layer molded rubber

Maximum Operating Pressure:

1000.0 pounds per square inch

Thread Size:

0.625 inches 1st end

Seat Angle:

45.0 degrees 1st end

Hydrostatic Test Pressure:

2000.0 pounds per square inch

Outer Covering Environmental Protection:

Mildew resistant and oil resistant and oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

22.300 inches

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A542a0