Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-728-3220

Cross Sectional Shape:	
Round	
Thread Class:	
2a 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.313 inches	
Tempurature Rating:	
-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response	
Outside Diameter:	
0.592 inches	
Connection Style:	
Swivel nut, inverted flare 1st end	
End Connection Design:	
Straight 2nd end	
Connection Type:	
Threaded external tube 1st end	
Thready Qty Per Inch (tpi):	
18 1st end	
Burst Test Pressure:	
4000.0 pounds per square inch	
Layer Composition And Location:	
1st layer braided steel wire and outer layer molded rubber	
Maximum Operating Pressure:	
1000.0 pounds per square inch	
Thread Size:	
0.625 inches 1st end	
Seat Angle:	
45.0 degrees 1st end	
Hydrostatic Test Pressure:	
2000.0 pounds per square inch	
Outer Covering Environmental Protection:	
Mildew resistant and oil resistant and oil resistant	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
22.300 inches	
Media For Which Designed:	
Fuel/oil, hydrocarbon single response	
Thread Series Designator:	
Unf 1st end	

NSN 4720-00-728-3220

Nonmetallic Hose Assembly - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A542a0