

View Online at <https://aerobasegroup.com/nsn/4720-00-729-4906>

Cross Sectional Shape:

Round

Inside Diameter:

1.781 inches

Temperature Rating:

-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response

Flange Thickness:

0.297 inches 2nd end

Outside Diameter:

2.094 inches

Minimum Inside Bending Radius:

3.590 inches

Exterior Color:

Natural

Angle Between Rigid Elbow Fittings In Deg:

28.0

Center To Center Distance Between Bolt Holes Along Width:

3.812 inches 2nd end

Center To Center Distance Between Bolt Holes Along Length:

3.812 inches 2nd end

Bolt Hole Quantity:

4 2nd end

Flange Length:

4.000 inches 2nd end

Flange Width:

4.000 inches 2nd end

Connection Style:

Raised swivel 2nd end

Bolt Hole Diameter:

0.328 inches 2nd end

Raised Face Height:

0.015 inches 2nd end

Raised Face Diameter:

2.750 inches 1st end

End Flange Construction:

Solid 2nd end

End Connection Design:

Elbow 2nd end

Connection Type:

Raised face flange 2nd end

Features Provided:

Electrostatic discharge capability and internal support

Burst Test Pressure:

1400.0 pounds per square inch

Layer Composition And Location:

1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

200.0 pounds per square inch

Hydrostatic Test Pressure:

600.0 pounds per square inch

Flow Angle:

50.0 degrees 2nd end

Outer Covering Environmental Protection:

Abrasion resistant and corrosion resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

18.625 inches working

Flange Style:

Rectangular (includes square) 2nd end

Special Features:

Internal support consists of a flat steel helically wound spring

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0