Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-729-6849

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.188 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 160.0 degrees fahrenheit single response
Outside Diameter:
0.406 inches
Minimum Inside Bending Radius:
2.000 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal hose 1st end
Features Provided:
Electrostatic discharge capability
Thready Qty Per Inch (tpi):
24 1st end
Burst Test Pressure:
1700.0 pounds per square inch
Layer Composition And Location:
1st layer braided cotton cord and outer layer molded rubber
Maximum Operating Pressure:
250.0 pounds per square inch
Thread Size:
0.375 inches 1st end
Inside Surface Condition:
Smooth
Measuring Method And Length:
72.000 inches working
Special Markings:
Lp
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Unf 1st end

NSN 4720-00-729-6849

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0

