NSN 4720-00-730-2748

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-730-2748

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.297 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 460.0 degrees fahrenheit single response
Outside Diameter:
0.632 inches
Minimum Inside Bending Radius:
5.000 inches
Exterior Color:
Natural
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Complete fitting stainless steel all ends
Fitting Component And Surface Treatment:
Complete fitting passivate 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Second End Relationship With First End:
Identical
Burst Test Pressure:
12000.0 pounds per square inch
First End Swivel Action Capability:
Not included
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.562 inches 1st end
External Protection Type And Location (non-core):

chafe guard, chloroprene rubber tubing

NSN 4720-00-730-2748

A542a0

Nonmetallic Hose Assembly - Page 2 of 2



Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
22.250 inches working
Special Features:
External protection type and location- chafe guard, chloroprene rubber tubing, inner conveying tube material-plastic,
polytetrafluoroethylene
Thread Series Designator:
Unjf 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: