NSN 4720-00-730-7371

Cross Sectional Shape:

Round

Smooth

Thread Class:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-730-7371

3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.188 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
0.312 inches
Minimum Inside Bending Radius:
2.000 inches
Angle Between Rigid Elbow Fittings In Deg:
155.0
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Elbow 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Electrostatic discharge capability Burst Test Pressure:
Burst Test Pressure:
Burst Test Pressure: 12000.0 pounds per square inch
Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location:
Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire
Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure:
Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch
Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size:
Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.500 inches 1st end
Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.500 inches 1st end Seat Angle:
Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.500 inches 1st end Seat Angle: 37.0 degrees 1st end
Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.500 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure:
Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.500 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 3000.0 pounds per square inch
Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.500 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 3000.0 pounds per square inch Flow Angle:
Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.500 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 3000.0 pounds per square inch Flow Angle: 45.0 degrees 1st end

NSN 4720-00-730-7371

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Le	enath:
-------------------------	--------

6.000 inches working

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

Yes - demil/mli

Fiig:

A542a0