## NSN 4720-00-730-9291

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-730-9291
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.312 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
0.438 inches
Minimum Inside Bending Radius:
4.000 inches
Angle Between Rigid Elbow Fittings In Deg:
180.0
Connection Style:
Swivel nut, flareless 1st end
End Connection Design:
Elbow 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
9000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:

0.562 inches 1st end

### Seat Angle:

12.0 degrees 1st end

#### **Hydrostatic Test Pressure:**

4500.0 pounds per square inch

#### Flow Angle:

45.0 degrees 1st end

#### **Outer Covering Environmental Protection:**

Corrosion resistant

#### **Inside Surface Condition:**

Smooth

# NSN 4720-00-730-9291

Nonmetallic Hose Assembly - Page 2 of 2



Measuring M	lethod And	Length
8.000 inches	working	

**Thread Series Designator:** 

Unf 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A542a0