## NSN 4720-00-731-1305

Nonmetallic Hose Assembly - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/4720-00-731-1305 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.750 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 1.250 inches **Minimum Inside Bending Radius:** 9.500 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **End Fitting Component And Material:** Complete fitting steel all ends **Connection Type:** Threaded internal tube 1st end **Features Provided:** Electrostatic discharge capability Thready Qty Per Inch (tpi): 12 1st end Second End Relationship With First End: Identical **Burst Test Pressure:** 12000.0 pounds per square inch First End Swivel Action Capability: Not included **Layer Composition And Location:** 1st layer spirally laid steel wire **Maximum Operating Pressure:** 3000.0 pounds per square inch **Thread Size:** 1.062 inches 1st end Seat Angle: 37.0 degrees 1st end

**Inside Surface Condition:** Smooth

## NSN 4720-00-731-1305

Nonmetallic Hose Assembly - Page 2 of 2



## Measuring Method And Length: 17.000 inches Special Features: Inner conveying tube material-rubber, synthetic Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Un 1st end Shelf Life: N/a Unit Of Measure: --Demilitarization: No

Fiig: A542a0