

View Online at <https://aerobasegroup.com/nsn/4720-00-731-2804>

Cross Sectional Shape:

Round

Inside Diameter:

1.380 inches

Flange Thickness:

0.360 inches 2nd end

Outside Diameter:

2.290 inches

Minimum Inside Bending Radius:

9.000 inches

Inner Conveying Tube Style:

Annular open-pitch corrugated

Exterior Color:

Natural

Center To Center Distance Between Bolt Holes Along Width:

1.808 inches 2nd end

Center To Center Distance Between Bolt Holes Along Length:

1.808 inches 2nd end

Bolt Hole Quantity:

4 2nd end

Flange Length:

2.460 inches 2nd end

Flange Width:

2.460 inches 1st end

Connection Style:

Plain swivel 2nd end

Bolt Hole Diameter:

0.266 inches 2nd end

End Flange Construction:

Solid 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Plain face flange 2nd end

Burst Test Pressure:

240.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

60.0 pounds per square inch

Hydrostatic Test Pressure:

120.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Outer Covering Environmental Protection:

Corrosion resistant

Measuring Method And Length:

18.750 inches working

Flange Style:

Rectangular (includes square) 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A542a0