Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-734-3043

| view Online at https://aerobasegroup.com/nsn/4/20-0      | U-134-3043          |
|--|---------------------|
| Cross Sectional Shape:                                   |                     |
| Round  |                     |
| Thread Class:  |                     |
| 2b 1st end   |                     |
| Thread Direction:  |                     |
| Right-hand 1st end                                       |                     |
| Inside Diameter:   |                     |
| 0.250 inches   |                     |
| Tempurature Rating:                                      |                     |
| -40.0 degrees fahrenheit and 250.0 degrees fahrenheit    | it single response  |
| Outside Diameter:  |                     |
| 0.484 inches   |                     |
| Connection Style:  |                     |
| Plain 2nd end  |                     |
| End Connection Design:                                   |                     |
| Straight 2nd end   |                     |
| Connection Type:   |                     |
| Threaded internal tube 1st end                           |                     |
| Thready Qty Per Inch (tpi):                              |                     |
| 20 2nd end   |                     |
| Burst Test Pressure:                                     |                     |
| 1600.0 pounds per square inch                            |                     |
| Layer Composition And Location:                          |                     |
| 1st layer braided cotton cord and outer layer molded     | rubber, synthetic   |
| Maximum Operating Pressure:                              |                     |
| 400.0 pounds per square inch                             |                     |
| Thread Size:   |                     |
| 0.500 inches 2nd end                                     |                     |
| Seat Angle:  |                     |
| 37.0 degrees 1st end                                     |                     |
| Hydrostatic Test Pressure:                               |                     |
| 800.0 pounds per square inch                             |                     |
| Outer Covering Environmental Protection:                 |                     |
| Abrasion resistant and light resistant and oil resistant | and ozone resistant |
| Inside Surface Condition:                                |                     |
| Smooth   |                     |
| Measuring Method And Length:                             |                     |
| 8.000 inches   |                     |
| Media For Which Designed:                                |                     |
| Fuel/oil, hydrocarbon single response                    |                     |
| Thread Series Designator:                                |                     |
|  |                     |

## NSN 4720-00-734-3043

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

