Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-735-0556

Cross Section	al Shape:
Round	
Thread Class:	
2b 1st end	
Thread Directi	on:
Right-hand 1st	end
Inside Diamete	er:
0.410 inches	
Tempurature F	Rating:
-40.0 degrees f	ahrenheit and 275.0 degrees fahrenheit single response
Outside Diame	eter:
0.766 inches	
Minimum Insid	le Bending Radius:
4.625 inches	
Exterior Color	
Black	
Connection St	yle:
Swivel nut flare	1st end
End Connection	on Design:
Straight 1st end	1
Connection Ty	/pe:
Threaded interr	nal tube 1st end
Features Prov	ided:
Reusable end f	ittings
Burst Test Pre	ssure:
8000.0 pounds	per square inch
Layer Compos	ition And Location:
1st layer braide	d corrosion resistant steel wire and outer layer rubber impregnated braided fabric
Maximum Ope	rating Pressure:
2000.0 pounds	per square inch
Thread Size:	
0.688 inches 1	st end
Seat Angle:	
37.0 degrees 1	st end
Hydrostatic Te	est Pressure:
4000.0 pounds	per square inch
Inside Surface	Condition:
Smooth	
Measuring Me	thod And Length:
13.000 inches	working
Media For Whi	ch Designed:
	carbon single response

Nonmetallic Hose Assembly - Page 2 of 2

AeroBase Group

Thread Series Designator:

Unc 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0