Nonmetallic Hose Assembly - Page 1 of 2



١	/iew Online at https://aerobasegroup.com/nsn/4720-00-735-5326
C	Cross Sectional Shape:
F	Round
Т	Fhread Class:
3	3b 1st end
Т	Thread Direction:
F	Right-hand 1st end
l	nside Diameter:
C	0.188 inches
Т	Cempurature Rating:
-	65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
C	Dutside Diameter:
C	0.516 inches
C	Connection Style:
S	Swivel nut flare 1st end
E	End Connection Design:
S	Straight 1st end
C	Connection Type:
Т	Threaded internal tube 1st end
E	Burst Test Pressure:
1	2000.0 pounds per square inch
L	ayer Composition And Location:
1	st layer braided steel wire and 2nd layer braided steel wire and outer layer rubber impregnated braided cotton cord
Ν	Maximum Operating Pressure:
3	3000.0 pounds per square inch
Т	Thread Size:
C	0.438 inches 1st end
S	Seat Angle:
3	37.0 degrees 1st end
ŀ	Hydrostatic Test Pressure:
6	6000.0 pounds per square inch
l	nside Surface Condition:
S	Smooth
Ν	Measuring Method And Length:
7	72.000 inches working
Т	Thread Series Designator:
ι	Jnf 1st end
S	Shelf Life:
Ν	N/a
ι	Jnit Of Measure:
-	-
۵	Demilitarization:
Ν	No

NSN 4720-00-735-5326

Nonmetallic Hose Assembly - Page 2 of 2

Fiig: A542a0

