

View Online at <https://aerobasegroup.com/nsn/4720-00-736-8189>

Cross Sectional Shape:

Round

Inside Diameter:

0.375 inches

Temperature Rating:

-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Outside Diameter:

0.750 inches

Minimum Inside Bending Radius:

1.750 inches

Hose Or Tubing Specification/std Data:

Sae j40, 40r2, type a standard (includes industry or association standards, individual manufactureer standards, etc.).

First End Fitting Specification/std Data:

Mil ms35746-1 standard (includes industry or association standards, individual manufactureer standards, etc.).

Connection Style:

Gladhand 1st end

End Fitting Component And Material:

Complete fitting stainless steel all ends

Fitting Component And Surface Treatment:

Complete fitting passivate 1st end

Connection Type:

Glad hand quick disconnect 1st end

Second End Relationship With First End:

Identical

Burst Test Pressure:

900.0 pounds per square inch

Layer Composition And Location:

Outer layer molded rubber, chloroprene

Hydrostatic Test Pressure:

200.0 pounds per square inch

Outer Covering Environmental Protection:

Fuel resistant and oil resistant and mildew resistant and cold resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

99.062 inches

Special Features:

Inner conveying tube material-rubber, synthetic

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0