

View Online at <https://aerobasegroup.com/nsn/4720-00-736-8189>

**Cross Sectional Shape:**

Round

**Inside Diameter:**

0.375 inches

**Tempurature Rating:**

-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

**Outside Diameter:**

0.750 inches

**Minimum Inside Bending Radius:**

1.750 inches

**Hose Or Tubing Specification/std Data:**

Sae j40, 40r2, type a standard (includes industry or association standards, individual manufactureer standards, etc.).

**First End Fitting Specification/std Data:**

Mil ms35746-1 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Connection Style:**

Gladhand 1st end

**End Fitting Component And Material:**

Complete fitting stainless steel all ends

**Fitting Component And Surface Treatment:**

Complete fitting passivate 1st end

**Connection Type:**

Glad hand quick disconnect 1st end

**Second End Relationship With First End:**

Identical

**Burst Test Pressure:**

900.0 pounds per square inch

**Layer Composition And Location:**

Outer layer molded rubber, chloroprene

**Hydrostatic Test Pressure:**

200.0 pounds per square inch

**Outer Covering Environmental Protection:**

Fuel resistant and oil resistant and mildew resistant and cold resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

99.062 inches

**Special Features:**

Inner conveying tube material-rubber, synthetic

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0