NSN 4720-00-736-9882

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-736-9882 **Cross Sectional Shape:** Round **Thread Class:** 2a 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.188 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response **Outside Diameter:** 0.438 inches **Minimum Inside Bending Radius:** 4.000 inches **Connection Style:** Swivel nut, inverted flare 1st end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded external tube 1st end Thready Qty Per Inch (tpi): 27 2nd end **Burst Test Pressure:** 1700.0 pounds per square inch **Layer Composition And Location:** 1st layer braided cotton cord and outer layer molded rubber **Maximum Operating Pressure:** 425.0 pounds per square inch **Thread Size:** 0.438 inches 1st end **Hydrostatic Test Pressure:** 850.0 pounds per square inch **Outer Covering Environmental Protection:** Fuel resistant and oil resistant **Inside Surface Condition:** Smooth **Measuring Method And Length:** 13.125 inches and 13.375 inches **Thread Series Designator:**

Uns 1st end

Shelf Life:

N/a

NSN 4720-00-736-9882

Nonmetallic Hose Assembly - Page 2 of 2



| ш | ın | 10 | <i>(</i>)+ | Measure: | |
|---|----|----|-------------|----------|--|
| | | | | | |

--

Demilitarization:

No

Fiig:

A542a0