

View Online at <https://aerobasegroup.com/nsn/4720-00-737-0837>

Cross Sectional Shape:

Round

Thread Class:

2b and 2a 1st end

Thread Direction:

Right-hand and right-hand 1st end

Inside Diameter:

0.125 inches

Temperature Rating:

-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Outside Diameter:

Between 0.469 inches and 0.500 inches

Exterior Color:

Black

Connection Style:

Inverted flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal and external tube 1st end

Thready Qty Per Inch (tpi):

24 and 18 1st end

Burst Test Pressure:

5000.0 pounds per square inch

Layer Composition And Location:

1st layer rubber impregnated braided cotton cord and 2nd layer rubber impregnated braided cotton cord and outer layer molded rubber, chloroprene

Thread Size:

0.437 inches and 0.625 inches 1st end

Seat Angle:

42.0 degrees 1st end

Hydrostatic Test Pressure:

4000.0 pounds per square inch

Outer Covering Environmental Protection:

Abrasion resistant and hydraulic solution resistant and mildew resistant and oil resistant and ozone resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

17.344 inches

Test Data Document:

63477-fe52380 to fe52399 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Uns and unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0