

View Online at <https://aerobasegroup.com/nsn/4720-00-737-3248>

Cross Sectional Shape:

Round

Thread Class:

2a 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.188 inches

Temperature Rating:

-65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

0.500 inches

Minimum Inside Bending Radius:

5.000 inches

Exterior Color:

Black

Connection Style:

Swivel nut, inverted flare 2nd end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded external tube 2nd end

Burst Test Pressure:

4500.0 pounds per square inch

Layer Composition And Location:

1st layer rubber impregnated braided cotton cord and 2nd layer rubber impregnated braided cotton cord and outer layer molded rubber, chloroprene

Maximum Operating Pressure:

1000.0 pounds per square inch

Thread Size:

0.500 inches 2nd end

Seat Angle:

45.0 degrees 2nd end

Hydrostatic Test Pressure:

3000.0 pounds per square inch

Outer Covering Environmental Protection:

Mildew resistant and oil resistant and oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

28.000 inches

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 2nd end

Specification Or Standard:

3/16 in. Id size

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0

Mil-std (military Standard):

Mil-h-13719 spec.