## NSN 4720-00-737-5038

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-737-5038

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.188 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.438 inches
Minimum Inside Bending Radius:
2.000 inches
Exterior Color:
Black
Connection Style:
Inverted flare 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
24 2nd end
Burst Test Pressure:
1100.0 pounds per square inch
Layer Composition And Location:
1st layer braided cotton cord and outer layer rubber impregnated braided rayon cord
Maximum Operating Pressure:
275.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
45.0 degrees 2nd end
Hydrostatic Test Pressure:
550.0 pounds per square inch
Outer Covering Environmental Protection:
Fuel resistant and oil resistant and mildew resistant and cold resistant
Inside Surface Condition:

5.000 inches

**Measuring Method And Length:** 

Smooth

## NSN 4720-00-737-5038

Nonmetallic Hose Assembly - Page 2 of 2



Media For Which Designe	þ	•
-------------------------	---	---

Fuel/oil, hydrocarbon single response

**Thread Series Designator:** 

Uns 2nd end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0