## NSN 4720-00-737-6000

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-737-6000

0 0 ( 10
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
Between 0.359 inches and 0.391 inches
Tempurature Rating:
65.0 degrees fahrenheit and 180.0 degrees fahrenheit single response
Outside Diameter:
Between 0.625 inches and 0.672 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
1000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided cotton cord
Maximum Operating Pressure:
150.0 pounds per square inch
Thread Size:
0.562 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
300.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
29.000 inches working
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Unf 1st end
Shelf Life:

N/a

## NSN 4720-00-737-6000

Nonmetallic Hose Assembly - Page 2 of 2



ı	1	:.	~	8.4			
ι	JN	ıτ	OI.	IVI	eа	เรเ	ıre:

--

Demilitarization:

No

Fiig:

A542a0