Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.cor	n/nsn/4720-00-738-4317
Cross Sectional Shape:	
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.250 inches	
Tempurature Rating:	
-40.0 degrees fahrenheit and 2000.0 deg	rees fahrenheit single response
Outside Diameter:	
Between 0.625 inches and 0.719 inches	
Connection Style:	
Swivel nut with compression sleeve 1st e	nd
End Connection Design:	
Straight 2nd end	
Connection Type:	
Unthreaded external tube 2nd end	
Burst Test Pressure:	
600.0 pounds per square inch	
Layer Composition And Location:	
1st layer braided asbestos cord and 2nd	layer braided asbestos cord and outer layer molded rubber, chloroprene
Thread Size:	
0.312 inches 1st end	
Seat Angle:	
12.0 degrees 1st end	
Outer Covering Environmental Protect	ion:
Fire retardant	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
10.500 inches excluding end fittings	
Outside Diameter Tube Accommodate	d:
0.250 inches 2nd end	
Thread Series Designator:	
Unf 1st end	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	

## NSN 4720-00-738-4317

Nonmetallic Hose Assembly - Page 2 of 2

**Fiig:** A542a0

