## NSN 4720-00-740-3659

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-740-3659 **Cross Sectional Shape:** Round **Thread Direction:** Right-hand 1st end **Inside Diameter:** 1.000 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 1.562 inches **Minimum Inside Bending Radius:** 12.000 inches **Connection Style:** Inverted flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded external pipe 1st end **Features Provided:** Electrostatic discharge capability **Burst Test Pressure:** 8000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, synthetic **Maximum Operating Pressure:** 2000.0 pounds per square inch **Thread Size:** 1.000 inches 1st end Seat Angle: 30.0 degrees 1st end **Outer Covering Environmental Protection:** Abrasion resistant and oil resistant and weatherproof **Inside Surface Condition:** Smooth **Measuring Method And Length:** 47.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response **Thread Series Designator:** Nptf 1st end

N/a

Shelf Life:

## NSN 4720-00-740-3659

Nonmetallic Hose Assembly - Page 2 of 2



ı	In	iŧ.	Ωf	м	دما	CII	re:
•	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		$\sim$	IVI	ca	Эu	ı c.

--

Demilitarization:

No

Fiig:

A542a0