

View Online at <https://aerobasegroup.com/nsn/4720-00-741-0489>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.875 inches

Temperature Rating:

-40.0 degrees fahrenheit and 275.0 degrees fahrenheit single response

Outside Diameter:

1.234 inches

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Electrostatic discharge capability

Thready Qty Per Inch (tpi):

14 1st end

Burst Test Pressure:

3200.0 pounds per square inch

Layer Composition And Location:

1st layer rubber impregnated cotton fabric and 2nd layer rubber impregnated cotton fabric and 3rd layer rubber impregnated cotton fabric and 4th layer braided cotton cord and 5th layer braided cotton cord and 6th layer braided steel wire and 7th layer spirally laid steel wire and outer layer rubber impregnated braided cotton cord

Maximum Operating Pressure:

800.0 pounds per square inch

Thread Size:

0.750 inches 2nd end

Seat Angle:

37.0 degrees 1st end

Outer Covering Environmental Protection:

Fire retardant and mildew resistant and oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

14.500 inches excluding end fittings

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Test Data Document:

19207-7410489 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Uns 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0