

View Online at <https://aerobasegroup.com/nsn/4720-00-741-0533>

**Cross Sectional Shape:**

Round

**Thread Class:**

2b and 2a 2nd end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.125 inches

**Temperature Rating:**

-40.0 degrees fahrenheit and 125.0 degrees fahrenheit single response

**Outside Diameter:**

0.484 inches

**Connection Style:**

Inverted flare 2nd end

**End Connection Design:**

Straight 2nd end

**Connection Type:**

Threaded internal and external tube 2nd end

**Layer Composition And Location:**

1st layer rubber impregnated braided cotton cord or 1st layer rubber impregnated braided polyamide cord or 1st layer rubber impregnated braided rayon cord and 2nd layer rubber impregnated braided cotton cord or 2nd layer rubber impregnated braided polyamide cord or 2nd layer rubber impregnated braided rayon cord and outer layer molded rubber, synthetic

**Maximum Operating Pressure:**

3000.0 pounds per square inch

**Thread Size:**

0.500 inches and 0.750 inches 2nd end

**Seat Angle:**

42.0 degrees 2nd end

**Outer Covering Environmental Protection:**

Cold resistant and ozone resistant and salt water resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

11.375 inches

**Media For Which Designed:**

Hydraulic fluid single response

**Thread Series Designator:**

Unf 2nd end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0