

View Online at <https://aerobasegroup.com/nsn/4720-00-741-0533>

Cross Sectional Shape:

Round

Thread Class:

2b and 2a 2nd end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.125 inches

Temperature Rating:

-40.0 degrees fahrenheit and 125.0 degrees fahrenheit single response

Outside Diameter:

0.484 inches

Connection Style:

Inverted flare 2nd end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded internal and external tube 2nd end

Layer Composition And Location:

1st layer rubber impregnated braided cotton cord or 1st layer rubber impregnated braided polyamide cord or 1st layer rubber impregnated braided rayon cord and 2nd layer rubber impregnated braided cotton cord or 2nd layer rubber impregnated braided polyamide cord or 2nd layer rubber impregnated braided rayon cord and outer layer molded rubber, synthetic

Maximum Operating Pressure:

3000.0 pounds per square inch

Thread Size:

0.500 inches and 0.750 inches 2nd end

Seat Angle:

42.0 degrees 2nd end

Outer Covering Environmental Protection:

Cold resistant and ozone resistant and salt water resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

11.375 inches

Media For Which Designed:

Hydraulic fluid single response

Thread Series Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0