

View Online at <https://aerobasegroup.com/nsn/4720-00-741-3492>

Cross Sectional Shape:

Round

Thread Class:

2b and 2a 1st end

Thread Direction:

Right-hand and right-hand 1st end

Inside Diameter:

0.188 inches

Temperature Rating:

-65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

Between 0.469 inches and 0.500 inches

Minimum Inside Bending Radius:

0.750 inches

Exterior Color:

Black

Connection Style:

Inverted flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal and external tube 1st end

Thread Qty Per Inch (tpi):

20 and 18 1st end

Burst Test Pressure:

4500.0 pounds per square inch

Layer Composition And Location:

1st layer rubber impregnated braided cotton cord and 2nd layer rubber impregnated braided cotton cord and outer layer molded rubber

Maximum Operating Pressure:

1125.0 pounds per square inch

Thread Size:

0.500 inches and 0.688 inches 1st end

Seat Angle:

42.0 degrees 1st end

Hydrostatic Test Pressure:

2250.0 pounds per square inch

Outer Covering Environmental Protection:

Mildew resistant and oil resistant and oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

19.000 inches and 19.250 inches

Media For Which Designed:

Hydraulic fluid nonpetroleum base single response

Thread Series Designator:

Unf and uns 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0