

View Online at <https://aerobasegroup.com/nsn/4720-00-753-9107>

Cross Sectional Shape:

Round

Thread Class:

2a 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

Between 0.234 inches and 0.266 inches

Temperature Rating:

-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Outside Diameter:

Between 0.421 inches and 0.453 inches

Connection Style:

Swivel nut, inverted flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded external tube 1st end

Burst Test Pressure:

1250.0 pounds per square inch

Layer Composition And Location:

1st layer braided cotton cord and outer layer rubber impregnated braided rayon cord

Maximum Operating Pressure:

300.0 pounds per square inch

Thread Size:

0.500 inches 1st end

Hydrostatic Test Pressure:

625.0 pounds per square inch

Outer Covering Environmental Protection:

Fuel resistant and cold resistant and mildew resistant and oil resistant and ozone resistant and vibration resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

15.000 inches

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unc 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0