

View Online at <https://aerobasegroup.com/nsn/4720-00-756-0475>

**Cross Sectional Shape:**

Round

**Thread Class:**

2b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.375 inches

**Temperature Rating:**

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

**Outside Diameter:**

0.750 inches

**Minimum Inside Bending Radius:**

1.750 inches

**Exterior Color:**

Black

**Connection Style:**

Swivel nut, inverted flare 1st end

**End Connection Design:**

Straight 2nd end

**Connection Type:**

Threaded internal tube 1st end

**Thready Qty Per Inch (tpi):**

20 1st end

**Burst Test Pressure:**

900.0 pounds per square inch

**Layer Composition And Location:**

1st layer rubber impregnated braided rayon cord and 2nd layer rubber impregnated braided rayon cord and outer layer molded rubber, chloroprene

**Maximum Operating Pressure:**

200.0 pounds per square inch

**Thread Size:**

0.688 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Hydrostatic Test Pressure:**

400.0 pounds per square inch

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

16.500 inches

**Special Features:**

Furnished with one reducer 0.688-20 un to 0.562-18 unf ext thds

**Media For Which Designed:**

Air single response

**Thread Series Designator:**

Unf 2nd end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0