Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-756-5197

| Cross Sectional Shape:   |
|--|
| Round  |
| Thread Class:  |
| 2b 1st end   |
| Thread Direction:  |
| Right-hand 1st end   |
| Inside Diameter:   |
| 1.000 inches   |
| Tempurature Rating:  |
| -40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response                    |
| Outside Diameter:  |
| 1.531 inches   |
| Minimum Inside Bending Radius:   |
| 12.000 inches  |
| Connection Style:  |
| Swivel nut flare 1st end   |
| End Connection Design:   |
| Straight 2nd end   |
| Connection Type:   |
| Threaded internal tube 1st end   |
| Features Provided:   |
| Reusable end fittings  |
| Burst Test Pressure:   |
| 8000.0 pounds per square inch  |
| Layer Composition And Location:  |
| 1st layer braided wire and 2nd layer braided wire and 3rd layer molded rubber, synthetic |
| Maximum Operating Pressure:  |
| 2000.0 pounds per square inch  |
| Thread Size:   |
| 1.312 inches 2nd end   |
| Seat Angle:  |
| 37.0 degrees 2nd end   |
| Hydrostatic Test Pressure:   |
| 4000.0 pounds per square inch  |
| Outer Covering Environmental Protection:   |
| Oil resistant and weatherproof   |
| Inside Surface Condition:  |
| Smooth   |
| Measuring Method And Length:   |
| 18.500 inches  |
| Media For Which Designed:  |
| Fuel/oil, hydrocarbon single response  |
|  |

Nonmetallic Hose Assembly - Page 2 of 2

**Thread Series Designator:** 

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0

