Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-756-9977

С	ross Sectional Shape:
R	bund
Tł	nread Class:
3b	o 1st end
Tł	nread Direction:
Ri	ght-hand 1st end
In	side Diameter:
0.	188 inches
Te	empurature Rating:
-6	7.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
0	utside Diameter:
0.	312 inches
C	onnection Style:
S١	wivel nut flare 1st end
Er	nd Connection Design:
St	raight 1st end
C	onnection Type:
T٢	nreaded internal tube 1st end
Fe	eatures Provided:
EI	ectrostatic discharge capability
B	urst Test Pressure:
12	2000.0 pounds per square inch
La	ayer Composition And Location:
0	uter layer braided corrosion resistant steel wire
M	aximum Operating Pressure:
15	500.0 pounds per square inch
Tł	nread Size:
0.	438 inches 1st end
Se	eat Angle:
37	7.0 degrees 1st end
In	side Surface Condition:
Sr	nooth
M	easuring Method And Length:
8.	500 inches working
Tł	nread Series Designator:
Uı	nf 1st end
Sł	helf Life:
N/	/a
Uı	nit Of Measure:
De	emilitarization:
N	n

NSN 4720-00-756-9977

Nonmetallic Hose Assembly - Page 2 of 2

Fiig: A542a0

