## NSN 4720-00-757-4818

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-757-4818

Ocean Oceaffer at Ohemes
Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.500 inches
Outside Diameter:
0.920 inches
Connection Style:
External seat for gasket seal (boss) 2nd end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal hose 1st end
Thready Qty Per Inch (tpi):
14 2nd end
Burst Test Pressure:
7000.0 pounds per square inch
Layer Composition And Location:
1st layer braided cotton cord and 2nd layer braided wire and outer layer rubber impregnated braided cotton cord
Maximum Operating Pressure:
1000.0 pounds per square inch
Thread Size:
0.875 inches 1st end
Hydrostatic Test Pressure:
1500.0 pounds per square inch
Flow Angle:
90.0 degrees 1st end
Outer Covering Environmental Protection:
Mildew resistant
Inside Surface Condition:
Smooth
Media For Which Designed:
Fuel/oil, hydrocarbon and hydraulic fluid and fuel/oil, hydrocarbon single response
Thread Series Designator:
Unf 1st end
Shelf Life:
N/a
Unit Of Magguro

--

## NSN 4720-00-757-4818

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0