NSN 4720-00-758-0635



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-00-758-0635 **Cross Sectional Shape:** Round **Thread Class:** 2b and 2a 2nd end Thread Direction: Right-hand 1st end **Inside Diameter:** 0.125 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.484 inches **Exterior Color:** Black **Connection Style:** Inverted flare 2nd end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded internal and external tube 2nd end **Burst Test Pressure:** 5000.0 pounds per square inch **Layer Composition And Location:** 1st layer rubber impregnated braided cotton cord and 2nd layer rubber impregnated braided cotton cord and outer layer molded rubber, chloroprene **Maximum Operating Pressure:** 1000.0 pounds per square inch **Thread Size:** 0.438 inches 1st end Seat Angle: 42.0 degrees 2nd end **Hydrostatic Test Pressure:**

2000.0 pounds per square inch

Outer Covering Environmental Protection:

Abrasion resistant and fuel resistant and hydraulic solution resistant and oil resistant and ozone resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

15.930 inches and 16.520 inches

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

NSN 4720-00-758-0635

Nonmetallic Hose Assembly - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A542a0