NSN 4720-00-758-7896



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-00-758-7896 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.375 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.625 inches **Minimum Inside Bending Radius:** 3.000 inches **Exterior Color:** Black **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 1600.0 pounds per square inch **Layer Composition And Location:** 1st layer braided rayon cord and outer layer molded rubber, chloroprene **Maximum Operating Pressure:** 400.0 pounds per square inch **Thread Size:** 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 800.0 pounds per square inch **Outer Covering Environmental Protection:** Oil resistant and weatherproof **Vacuum In Torr:** 254.0 **Inside Surface Condition:**

Smooth **Measuring Method And Length:** 9.562 inches

NSN 4720-00-758-7896

Nonmetallic Hose Assembly - Page 2 of 2



Thread	Series	Designator:
--------	--------	--------------------

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0