Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-758-9038

Cross Sectional Shape:	
Round	
Thread Class:	
2b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.313 inches	
Tempurature Rating:	
-40.0 degrees fahrenheit and 275.0 degrees fahrenheit single response	
Outside Diameter:	
0.766 inches	
Minimum Inside Bending Radius:	
4.000 inches	
Connection Style:	
Swivel nut flare 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Burst Test Pressure:	
9000.0 pounds per square inch	
Layer Composition And Location:	
1st layer braided cotton cord and 2nd layer braided wire and outer layer rubber impregnated woven fab	oric
Maximum Operating Pressure:	
2250.0 pounds per square inch	
Thread Size:	
0.562 inches 1st end	
Seat Angle:	
37.0 degrees 1st end	
Vacuum In Torr:	
28.0	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
20.250 inches	
Media For Which Designed:	
Fuel/oil, hydrocarbon single response	
Thread Series Designator:	
Unf 1st end	
Shelf Life:	
N/a	

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0