Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-759-6660

Cross Section	onal Shape:
Round	
Thread Clas	S:
3b 1st end	
Thread Direct	ction:
Right-hand 1	st end
Inside Diamo	eter:
0.187 inches	
Tempurature	e Rating:
-65.0 degree	s fahrenheit single response and 400.0 degrees fahrenheit single response
Outside Diar	neter:
0.520 inches	
Minimum Ins	side Bending Radius:
3.000 inches	
Connection	Style:
Swivel nut fla	re 2nd end
End Connec	tion Design:
Straight 1st e	nd
Connection	Туре:
Threaded inte	ernal tube 1st end
Thready Qty	Per Inch (tpi):
20 2nd end	
Burst Test P	ressure:
12000.0 pour	nds per square inch
Layer Comp	osition And Location:
Outer layer m	nolded polytetrafluoroethylene
Maximum O	perating Pressure:
3000.0 pound	ds per square inch
Thread Size:	
0.438 inches	1st end
Hydrostatic	Test Pressure:
6000.0 pound	ds per square inch
Flow Angle:	
90.0 degrees	2nd end
Inside Surfa	ce Condition:
Smooth	
Measuring M	lethod And Length:
16.200 inche	s working
Thread Serie	es Designator:
Unf 2nd end	
Shelf Life:	
N/a	

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0