Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-760-5512

Cross Sectional Shape:	
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.375 inches	
Tempurature Rating:	
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response	
Outside Diameter:	
0.625 inches	
Minimum Inside Bending Radius:	
3.000 inches	
Exterior Color:	
Black	
Connection Style:	
Swivel nut flare 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Features Provided:	
Reusable end fittings	
Burst Test Pressure:	
1000.0 pounds per square inch	
Layer Composition And Location:	
1st layer braided cotton cord and outer layer rubber impregnated braided cotton of	cord
Maximum Operating Pressure:	
250.0 pounds per square inch	
Thread Size:	
0.625 inches 1st end	
Seat Angle:	
37.0 degrees and 45.0 degrees 1st end	
Hydrostatic Test Pressure:	
500.0 pounds per square inch	
Outer Covering Environmental Protection:	
Mildew resistant and oil resistant	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
93.750 inches	



Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0