

NSIN 4720-00-701-2907 Nonmetallic Hose Assembly - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/4720-00-761-2967
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.625 inches
Tempurature Rating:
-67.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Flange Thickness:
0.297 inches 2nd end
Outside Diameter:
0.781 inches
Minimum Inside Bending Radius:
6.500 inches
Center To Center Distance Between Bolt Holes Along Width:
1.156 inches 2nd end
Center To Center Distance Between Bolt Holes Along Length:
1.156 inches 2nd end
Bolt Hole Quantity:
4 2nd end
Flange Length:
1.594 inches 2nd end
Flange Width:
1.594 inches 2nd end
Connection Style:
Swivel nut, flareless 1st end
Bolt Hole Diameter:
0.205 inches 2nd end
End Flange Construction:
Solid 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:

5000.0 pounds per square inch



Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

# Maximum Operating Pressure:

1000.0 pounds per square inch

### Thread Size:

1.062 inches 1st end

### Seat Angle:

37.0 degrees 1st end

# Hydrostatic Test Pressure:

2000.0 pounds per square inch

### Flow Angle:

90.0 degrees 2nd end

# Outer Covering Environmental Protection:

Corrosion resistant

# Inside Surface Condition:

Smooth

#### Measuring Method And Length:

46.000 inches working

#### Flange Style:

Rectangular (includes square) 2nd end

#### **Supplementary Features:**

This item has been reviewed for asbestos material. The current approved source, 78286, has indicated their part number contained

asbestos prior to 1984. They continue to manufacture the same part number without asbestos material after 1984

# Thread Series Designator:

Unj 1st end

### Shelf Life:

N/a

# Unit Of Measure:

```
---
```

# Demilitarization:

Yes - demil/mli

# Fiig:

A542a0